



## Features

- Secured By Design & Part Q as standard
- 3 Low threshold design options
- Mechanical outer frame and threshold joint
- Suited hardware range
- Low sightline glazing gaskets
- Unique rebate system
- 13 Opening configurations
- Replicates existing bevel design

## Benefits

- High security performance and peace of mind
- Versatile, designed to suit any application
- Ease of construction, transport and installation
- Improved aesthetics
- Larger glass area
- Smaller Sash width with increased adjustment
- More choice to maximise sales
- Matches existing Diamond Suite

## Specification

### 7 Standard Colour Options

	Black 9005
	Dark Grey 7016
	Slate Grey 7015
	Cream 9001
	White 9016
	Black on White
	7016 Dark Grey on White

### Hardware

- Shootbolt locking on all doors
- 3 Hook locking on master sash
- All hardware tested to Secured by Design standards
- All gearing is concealed

### Handles & Magnets

- Black
- White
- Gold
- Chrome

### Hinge Finishes

- Black as standard
- White option available

### Bespoke Options

- Coloured through threshold option
- Bespoke System- unique to UK Windows & Doors Group

### Energy Performance & U Values

Unit Size	U Value
28mm	1.8
36mm	1.6

### Minimum and Maximum Sizes Per Sash

Min. Width	Max. Width
510mm	1200mm

### Minimum and Maximum Outer Frame Sizes

Min. Width	Max. Width
1212mm - 2 pane	6176mm - 6 pane
Min. Height	Max. Height
1820mm	2460mm

## Size and Configuration Options

The table to the right gives minimum and maximum size limitations for each Bi-Fold Door style.

Width (mm)	Door Styles												
	2-2-0	3-3-0	3-2-1	4-4-0	4-3-1	4-2-2	5-5-0	5-4-1	5-3-2	6-6-0	6-5-1	6-4-2	6-3-3
Minimum	1212	1670	1734	2256	2192	2319	2714	2278	2778	3300	3236	3363	3236
Maximum	2466	3738	3618	4761	4952	4824	6164	5913	5913	5855	6176	5926	6176